

Technical Data Sheet

Continuous LED Panel Indication Lamp 22.5mm
Flashing LED Panel Indication Lamp 22.5mm

Features

- Optically Enhanced Lens
- Press Fit Lens Design
- Compact Size
- Multiple Voltage Range
- Low Current Consumption
- Touch -Safe Screw Terminal connection
- Available in 7 Colors : Red, Yellow, Blue, Green, Amber, Clear, White



Technical data

Mechanical	Lens Fitment	Press Fit
	Lens type	Refracted
	Lens Material	Polycarbonate
	Housing Material	Nylon
	Gasket Material	Silicon
	Length inside panel	36 mm
	Termination	Steel Alloy Screw With Captive Washer, Cu-Ni Plated
	Recommended Terminal screw Tightening Torque	1.25 Nm
Electrical	Voltage	ACV - 24, 30, 48, 60, 110/120, 220/240, 415 DCV - 24, 48, 110/120, 220/240
	Voltage Variation	+/- 20% of nominal supply Voltage
	Wide Voltage Band	24-240 V AC/DC
	Polarity Protection	Polarity Protection for DC Lamps
	Flash Rate	1-2 Hz Fixed (For Flashing LED Lamps)
	Insulation resistance at 500 VDC	1.3 X 10 ⁴ Mega - Ohm
	Burning Hours / Service Life @ 25°C, at rated voltage	100000 Hrs
	Terminal Capacity Flexible Wire Solid conductor Wire	2 X 0.5 to 2.5 mm ² (Max) 2 X 0.5 to 2.5 mm ² (Max)
	Certifications	CE
	Degree of Protection	IP 55 - Front, IP20 - Rear

Product Dimension Drawing

